

微電腦型盤面式控制電錶(24x48mm) (MICROPROCESS PANEL CONTROLLER METER)(24x48mm)

MODEL
MMX-AS

CE



■特點(FEATURES)

- 精確度 0.05% 滿刻度 ± 1位數 (Accuracy 0.05% F.S. ± 1digit)
- 可量測 交流電流/交直電壓/電位計/傳送器/Pt-100/荷重元/電阻 等信號 (Measuring DCA/DCV/ACA/ACV/Potentiometer/Transmitter/Pt-100/Load Cell/Resistor/etc.....)
- 顯示範圍-19999~99999 可任意規劃 (Programmable range -19999~99999 digit)
- 具有自動歸零/保持/開根號功能 (Auto zero/hold/ROOT function)
- 2組警報功能 (Max. two alarm function) (optional)
- 16BIT 類比輸出功能 (16 bit DAC analog output function) (optional)
- 數位RS-485界面 (Digit RS-485 interface function) (optional)

1.MODEL:MMX-AS □ □□ - □ □□□

(選購型號)

NO	Input Type	NO	DCV(ACV)	NO	DCA(ACA)	NO	Potentiometer	NO	Load Cell	NO	Alarm output	NO	Analog output	NO	RS-485	NO	Aux. Power
A	DC	11	0-50mV	21	0-19.999uA	31	0-10%	61	2mV/V	0	None	0	None	N	None	A	AC/DC18-60V
B	AC(RMS)	12	0-5V	22	0-199.99uA	32	0-50%	62	3mV/V	1	One	1	DC4-20mA	Y	RS-485	B	AC/DC90-260V
C	AC(TRMS)	13	0-10V	23	0-1.9999mA	33	0-100%	63	2mV/V	2	Two	2	DC0-10V				
D	Potentiometer	14	0-36V	24	0-19.999mA	34	5-95%	64	3mV/V			9	SPECIFIED				
E	Transmitter	15	0-54V	25	0-199.99mA	35	10-90%	69	SPECIFIED								
F	Pt-100(RTD)	16	0-110V	26	0-1.9999A	39	SPECIFIED			• 61/62 Exciting DC5V(<50mA)	Relay contact (AC250V-2.5A, DC30V-5A)						• Modbus mode
G	Thermocouple	17	0-600V	27	0-5.000A		Three wire connection			• 63/64 Exciting DC10V(<50mA)							• Less 4VA for AC/DC input
H	Load Cell	19	SPECIFIED	29	SPECIFIED		Exciting voltage DC2.5V(<10mA)										
R	Resistor																

2.SPECIFICATION (主要規格)

- Measuring accuracy : 0.05% F.S. ± 1 digit
(精確度) (23 ± 5°C) 0.2% F.S. ± 1 digit (AC(RMS))
0.2% F.S. ± 0.5°C (CJC) (Thermocouple)
- Sampling time : 16 cycles/sec.
(取樣時間)
- Readout range : -19999 ~ 99999 digit adjustable
(顯示值範圍)
- Alarm delay time : 0-99.9 second adjustable
(繼電器延遲動作時間)
- Alarm action : HI or Lo adjustable
(繼電器動作方向)
- Relay contact output : AC 250V-2.5A, DC 30V-5A
(繼電器容量)
- Analog output resolution : 16 bit DAC
(類比輸出解析度)
- Response time : < 250ms (0-90%)
- Output drive capability : < 10mA for voltage mode
< 10V for current mode
- Output ripple (p-p) : < 0.1% F.S.
- RS-485 address : "01"- "FF"
- RS-485 baud rate : 19200/9600/4800/2400 selective
- RS-485 protocol : Modbus RTU mode
- Temp. coefficient : 50ppm/°C (0-50°C)
- Display : Red high efficiency LEDs high 10.16mm (0.4")
- Parameter setting : Touch switches
- Memory mode : Non-volatile E² PROM memory
- Dielectric strength : 1.5KVac/1 min. (input/output/power)
1600 Vdc (input/output)
- Operating condition : 0-50°C (20 to 90% RH non-condensed)
- Storage condition : 0-70°C (20 to 90% RH non-condensed)
- CE EMC Certification : EN 55022:1998/A1:2000 Class A
EN 61000-3-2:2000
EN 61000-3-3:1995/A1:2001
EN 55024:1998/A1:2001

3. OUTSIDE DIMENSION AND CONNECTION DIAGRAM

(外型尺寸與開孔尺寸與配線圖)

