

## Elmasteam 4.5 basic

Reliability and quality made in Germany

### Elma Order Nos.

Elmasteam 4.5 basic with fixed nozzle and foot switch	106 8874
Elmasteam 4.5 basic HP with hand piece (1,3 m)	106 8907
Wall bracket	105 8677



The compact Elmasteam 4.5 basic is ideally suitable for performing all occurring precleaning and final cleaning in the watch and jewellery industry and in the general workshop area.

The pressure tank is filled in a simple way using the filling tray. The indirect heater is located outside the pressure tank, lime deposits on the heater are prevented and the service life is increased.

Occurring deposits in the tank due to hard water can be removed easily and quickly through the safety ball valve using a rinsing set.

Scope of delivery: tweezers; sieve; maintenance hose; rinsing set; 1x tank cap with safety valve

### Product Features

- 3 years warranty
- 4.5 bar pressure with maximum safety technology
- Constant steam availability due to high heat output
- Optimum for use as well as for small spaces
- Variant can be selected between fixed nozzle or flexible hand piece
- Machine and safety devices with CE certification and TÜV type approval according to DIN EN 61010-1
- No external water connection is necessary due to manual filling
- Prevention of lime deposits on the heater
- Easy operation and clear display

### Technical Data

Mains voltage (V)	220 - 240	Pressure tank volume (litres)	4
Mains frequency (Hz)	50 / 60	Max. filling volume (litres)	3.3
Max. power consumption (W)	2800	Operating pressure (bar)	4.5
Rated power at 230 V (W)	2130	Dimensions W x D x H (mm)	245 / 305 / 320
Case material	PC/ABS	Steam temperature in the boiler (°C)	155
Weight empty (kg)	6.75	Steam temperature at the nozzle (°C)	135