


Datasheet

mSATA 3SE3 series

- SATA 6.0 Gb/s interface
- iSMART disk health monitoring
- Intelligent error recovery system
- Excellent data transfer speed
- Zero mechanical interference
- Anti-vibration mechanical design
- JEDEC standard MO-300 dimension



Introduction

Innodisk mSATA 3SE3 is designed with mSATA form factor by MO-300/MO-300B which established by JEDEC, and support SATA III standard (6.0 Gb/s) with excellent performance. Regarding of mechanical interference, Innodisk mSATA 3SE3 absolutely replaces the traditional hard disk and makes personal computer, in any field, smaller and easier.


Innodisk mSATA 3SE3 effectively reduces the booting time of operation system and the power consumption is less than hard disk drive (HDD), and complies with ATA protocol, no additional drives are required, and can be configured as a boot device or data storage device.

mSATA 3SE3 series

Contact us for more information about the mSATA 3SE3.

Innodisk is a service-driven provider of industrial embedded flash storage products and technologies, with a focus on the cloud computing, industrial/embedded, and aerospace and defense industries.

Diagram



Specifications

Headquarters (Taiwan)

5F., No. 237, Sec. 1, Datong Rd., Xizhi Dist., New Taipei City 221, Taiwan (R.O.C.)
Tel: +886-2-77033000
Email: sales@Innodisk.com

Branch Offices:

USA
usasales@Innodisk.com
+1-510-770-9421
Europe
esusales@Innodisk.com
+31-(0)40-282-1818
Japan
jpsales@Innodisk.com
+81-3-6667-0161
China
sales_cn@Innodisk.com
+86-755-21673689
www.Innodisk.com

© 2016 Innodisk Corporation.
All right reserved. Specifications are subject to change without prior notice.

20160920

Interface	SATA III
Flash Type	SLC
Capacity	04GB~128GB
Max. Channels	4
Sequential R/W (MB/sec, max.)	385/225
Max. Power Consumption	0.5 W (3.3V x 180 mA)
Thermal Sensor	ST- Optional /WT- Default
TRIM	√
External DRAM buffer	-
H/W Write Protect	-
ATA Security	√
S.M.A.R.T.	√
Dimension (WxLxH)	29.8 X 50.8 X 3.4 mm
Environment	Vibration: 20G @7~2000Hz Shock: 1500G @ 0.5ms Storage Temperature: -55°C ~ +95°C MTBF: 3 million hours

Ordering Information

Operation Temp.	04GB	08GB	16GB	32GB	64GB	128GB
Standard Grade (0°C ~ +70°C)	DEMSR-04GD08SCASB	DEMSR-08GD08SCADB	DEMSR-16GD08SCAQB	DEMSR-32GD08SCAQB	DEMSR-64GD08SCAQB	DEMSR-A28D08SCAQB
Industrial Grade (-40°C ~ +85°C)	DEMSR-04GD08SWASB	DEMSR-08GD08SWADB	DEMSR-16GD08SWAQB	DEMSR-32GD08SWAQB	DEMSR-64GD08SWAQB	DEMSR-A28D08SWAQB