

## ExxonMobil™ PP9574E6

# Polypropylene Random Copolymer

#### **Product Description**

A highly clarified random copolymer resin designed for general purpose injection molding applications requiring resistance to buildup of static electricity.

General					
Availability <sup>1</sup>	<ul> <li>North America</li> </ul>				
Features	<ul> <li>Antistatic</li> </ul>		<ul> <li>Ethylene Oxide Sterilizable</li> </ul>		
	<ul> <li>Controlled Rheology</li> </ul>	<u>'</u>	<ul> <li>High Clarity</li> </ul>		
Uses	• Caps		<ul> <li>Medical/Healthcare</li> </ul>	<ul> <li>Rigid F</li> </ul>	Packaging
	<ul> <li>Closures</li> </ul>		Applications <sup>2</sup> • Packaging		
Appearance	<ul> <li>Natural Color</li> </ul>				
Form(s)	<ul> <li>Pellets</li> </ul>				
Processing Method	<ul> <li>Injection Molding</li> </ul>				
Revision Date	<b>1</b> 1/01/2010				
Physical	Typical Value	(English)	Typical Value	(SI)	Test Based On
Melt Mass-Flow Rate (MFR) (230°C/2.16 kg	g) 12	g/10 min	12	g/10 min	ASTM D1238
Density	0.900	g/cm³	0.900	g/cm³	ExxonMobil Method
Mechanical	Typical Value	(English)	Typical Value	(SI)	Test Based On
Tensile Strength at Yield					ASTM D638
2.0 in/min (51 mm/min)	4140	psi	28.5	MPa	
Elongation at Yield (2.0 in/min (51 mm/min	)) 13	%	13	%	ASTM D638
Flexural Modulus - 1% Secant					
0.051 in/min (1.3 mm/min)	144000	psi	993	MPa	ASTM D790A
0.51 in/min (13 mm/min)	177000	psi	1220	MPa	ASTM D790B
mpact	Typical Value	(English)	Typical Value	(SI)	Test Based On
Notched Izod Impact (73°F (23°C))	1.6	ft·lb/in	88	J/m	ASTM D256A
Thermal	Typical Value	(English)	Typical Value	(SI)	Test Based On
Deflection Temperature Under Load (DTUL at 66psi - Unannealed		_	76.2	°C	ASTM D648
Hardness	Typical Value	(English)	Typical Value	(SI)	Test Based On
Rockwell Hardness	84	. 5 /	84	,	ASTM D785

### Legal Statement

Contact your ExxonMobil Chemical Customer Service Representative for potential food contact application compliance (e.g. FDA, EU, HPFB).

#### Notes

Typical properties: these are not to be construed as specifications.

Effective Date: 11/01/2010 ExxonMobil Page: 1 of 2

<sup>&</sup>lt;sup>1</sup> Product may not be available in one or more countries in the identified Availability regions. Please contact your Sales Representative for complete Country Availability.

 $<sup>^2</sup>$  This product, including the product name, shall not be used or tested in any medical application without the prior written acknowledgement of ExxonMobil Chemical as to the intended use. For detailed Product Stewardship information, please contact Customer Service.