



No.	PinName	No.	PinName
1	ESD(GND)	24	V1
2	VOUT	25	V2
3	CE2P	26	VC
4	CE2N	27	VSS
5	CE3P	28	VDDA
6	CE1N	29	VDDI
7	CE1P	30	VD1
8	V3	31	sda_out[0:23]
9	CB1P	32	sda_in[0:1]
10	CB1N	33	SCLK
11	MV3	34	A0
12	CD2P	35	RSTB
13	CD2N	36	CSB
14	NAVDD	37	TP1
15	CD1N	38	TP2
16	CD1P	39	BL_K
17	CA2N	40	BL_A
18	CA2P	41	NC
19	CA1N	42	NC
20	CA1P	43	NC
21	AVDD	44	NC
22	MV2	45	ESD(GND)
23	MV1		

*1. LCD Display Type	FSTN, Transflective, Positive	*6. Storage Temp	-30°C~80°C
*2. Viewing Direction	6H	*7. Driver IC	ST75320/(4-line SPD)
*3. LCD Driver Mode	1/240Duty, 1/17Bias	*8. Backlight	WHITE Vf=12.0V If=30mA
*4. Operating Voltage	3.3V	*9. RDHS	YES
*5. Operating Temp	-20°C~70°C		

**HOT DISPLAY**

Dwg Title: HTG320240A  
EDC No: 10200381  
Scale: 1:1  
Unit: mm  
Ver: A/0  
Drawn: LIWEI  
Checked:  
Date: 2016-01-12